

Split Type Air Water Generator

ASAWG-A70(POU+Dehumidifier)

Specifications	Power Supply	AC220V/50Hz , 110V/60Hz
	POU	Hot Water Capacity: 85°C 90°C, 5L/H (Child Lock)
		Cold Water Capacity: 4°C- 10°C, 3.5L/H
		HotTank: 1.5L, Heating Power: 500W
		Cold Water Tank: 2L Cooling Power: 80W- 98W
	Top storage Tank: 11L with UV Bottom storage tank: 25L with UV	
Dehumidifier	Generation Power: 700W	
	Collection tank: 2L with UV light	
Compressor	POU	Huayi, R134a, 3 Years Warranty
	Dehumidifier	R410a
Materials		Korea Plastic Injection Technology Drawing Water Tank Stainless Steel 304
Water Capacity(30% 80%RH)		70L/ Day(30% ,80%RH)
Air Circulation		850m ³ /hr
Working condition	Temperature	5°C-38°C
	Humidity	28%-95%
Product size(mm)	POU	17.0/18.0(Kgs)
	Dehumidifier	27.0/30.0(Kgs)
Container Load 40ft		120Units
Filtration system		PP+Pre-carbon+UF+Post-carbon



Production lead time	50 days after receipt deposit
----------------------	-------------------------------

Mark:		
1. Attractive Streamlined Design	2. Compact Inner Configuration, Low Noise When in Working	3. Screen Type Control System
4. Child Lock Protection	5. Only one control system for two machines, the control system installed in POU	